



High-Bay

INTENDED USE

The Sharp DL-HB9 Series High-Bay for ambient lighting.

APPLICATION

The DL-HB9 Series luminaire is a high efficacy LED lighting solution perfectly suited for high-bay applications.

CONSTRUCTION

The housing consists of a durable extruded aluminum body assembled with a highly conductive extruded aluminum heat sink.

OPTIC

Durable, high efficiency glass optic ensures long life performance.

LED DRIVER

High Efficiency, long life driver.

WARRANTY

5 year limited warranty

RATED LIFE

Calculated Lumen Maintenance, 100,000 hrs

PERFORMANCE SUMMARY

- Delivered Lumens (nom) 24,071 lm
- Efficacy 100 lm/W
- Color Accuracy (CRI) 77
- Color Appearance (CCT) 5700K
- Center Beam Candelpower (CBCP) 7706 cd
- Spacing Criterion 0-180 1.3
- Spacing Criterion 90-270 1.3
- Input Power 241W
- Input Voltage 120-277V, 347-480V
- EMI FCC Compliant

WEIGHT

29.5 lbs

CERTIFICATIONS/LISTINGS

Damp Locations.



Not all product configurations are listed with Designlights Consortium. Please refer to http://www.designlights.org/solidstate.about.QualifiedProductsList_Publicv2.php for listed configurations.

Subject to change without notice.




DATE _____ TYPE _____

FIRM NAME _____

PROJECT _____

COMMENTS _____

DL-HB9 High-Bay



Model Combination Tables

Example : DL-HB9JP4

DL-HB	9	J	P	
Product Classification / Size / Optics	Product Size	Lumens	Color Temperature / CRI	Voltage
DLHB High Bay Fixture	9 Square	J 20,000-23,999	P 5700K	4 120-277 V LED Lamps/Fixture
				7 347-480 V LED Lamps/Fixture

SHARP ELECTRONICS CORPORATION
 Sharp Plaza Blvd., Memphis, TN 38193
 1-877-312-5331 • Email: LEDsupport@sharpusa.com
www.sharpledlighting.com